









GLOBAL Weighing

Approved Load Cells for hazardous locations



Type		Europe				FM (USA) + CSA (Canada) Class I, II, II Div 1, Group A, B, C, D, E, F, G T5 at Tmax=55 oC, T4A at Tmax=70 oC
		Zone 0	Zone 1	Zone 20 + 21	Zone 2 + 22	
	PR 6201 - standard PR 6221 - standard				Manufacturer Certificate	Approved
	PR 6201 - Ex ver. (/E) PR 6221 - Ex ver. (/E)	PTB 02 ATEX 2059 II 1 G Eex ia IIC T6		TÜV 03 ATEX 2301X II 1 D IP65 85 oC		
	PR 6201 LA					
	PR 6211/31...32 D1				Manufacturer Certificate	Approved
	PR 6211/52...14D1					
	PR 6211 LT					
	PR 6211/52...14 D1E	PTB 02 ATEX 2059 II 1 G Eex ia IIC T6		TÜV 03 ATEX 2301X II 1 D IP65 85 oC	Manufacturer Certificate	Approved
	PR 6241+PR6246 Standard				Manufacturer Certificate	Approved
	PR 6241+PR6246 Ex ver.	PTB 02 ATEX 2059 II 1 G Eex ia IIC T6		TÜV 03 ATEX 2301X II 1 D IP65 85 oC		
	PR 6251 LE Ex ver.		PTB 00 ATEX 2039 II 2 G Eex ia IIC T6	TÜV 03 ATEX 2301X II 1 D IP65 85 oC	Manufacturer Certificate	Approved
	PR 6251 L					
	PR 6251 LA					
	MP 56			TÜV 03 ATEX 2301X II 1 D IP65 85 oC	Manufacturer Certificate	
	MP42 / MP47 / MP49 MP52 / MP57 / MP59				Manufacturer Certificate	

Updated: 05/2006